

HLT SERIES CHAIRS

Tubular base/attached foot ring/backrest tilt and height adjustable.

HLT chairs are recommended for use in healthcare, educational, industrial, office and static control settings.

Manufactured with a sewn seam, the HL series marks a stylistic departure from many of our products, yet they feature the same level of durability common to all BioFit chairs. If staying ahead of the curve

in terms of aesthetics and performance is important to you, this line will keep you in the lap of luxury. Different options and upholstery combinations are available.

STANDARD FEATURES

Backrest: Ergonomic backrest with sewn seams and lumbar support, 15 1/2" wide x 14 1/2" high.

Seat: Ergonomic, four way contoured seat with sewn seams and waterfall front, 18 1/2" wide x 17" deep x 3".

Controls: Standard with Task Control – Soft-touch pneumatic seat-height adjustment, fixed rearward seat tilt of 3 1/2°, backrest tilt, backrest-height adjustment.

Base: Rugged 5-legged tubular steel base with 20" diameter attached footring, 23" leg spread.

Casters and Glides: Models available standard with casters have an R following the model number/manufacturing code. The remaining models are standard with nickel-plated glides. Standard casters are a single-wheel ball bearing caster for hard floors; many other optional casters/glides are available.

Fire Retardant: Meets California Technical Bulletin 117.

Upholstery: A wide range of upholstery fabrics are available to meet your needs.

Metal Parts: HLT Series chairs have a powder-coated finish as standard or a chrome-plated finish when specified with a C option code.



SEAT HEIGHT RANGES

Adj. Range	Model# Mfg. Code
17"-22"	HLT1722
17"-22**	HLT1722-R
19"-24**	HLT1924-R
19"-26"	HLT1926
19"-26**	HLT1926-R
21"-26"	HLT2126
21"-28**	HLT2128-R
23"-28**	HLT2328-R
25"-30"	HLT2530
27"-32**	HLT2732-R
29"-34††	HLT2934

OPTIONS/UPHOLSTERY

Additional Paint Finish Options	SPF
Seat Controls	EXE, FFAC
Armrests	ARS, ARU, PSAS, PSAU
Casters and Glides	BPG, CRC, GFR, LKRO, LKRU, LRO, LRU, MLR, NGC, NSG, R, STR, XR
Fire Retardant Options	C133
Miscellaneous	SW, TKB
Footrings	G

CRITICAL ENVIRONMENTS

Static Control